

## Wire Probe Test:

1. Connect alligator clip to good ground.
2. Activate a function (i.e. turn signal, lights or brakes).
3. Firmly grasp the corresponding function wire.
4. Pierce wire through insulation
5. Red light glows if wire has power

## Connector Test:

1. Connect alligator clip to ground terminal on socket
2. Activate a function (i.e. turn signal, lights or brakes).
3. Insert tester into each corresponding function hole on socket.
4. Red light glows if installation is correct

## Tips:

- If light does not glow, check ground connection.
- Ensure that you pierced insulation and reached copper strands.

## Prueba del alambre de prueba:

1. Conecte clip de lagarto a una buena tierra.
2. Active una funcion (ejemplo: señal de vuelta, luces o frenos).
3. Sujete firmemente el alambre de la funcion correspondiente.
4. Perfore el alambre por el aislante.
5. La luz roja brilla si el alambre tiene corriente.

## Prueba al conector:

1. Conecte el clip lagarto en la terminal de tierra en el conector.
2. Active una funcion (por ejemplo: señal de vuelta, luces o freno).
3. Inserte el probador en la cavidad correspondiente a cada funcion en el conector.
4. La luz roja brilla si la instalacion es correcta.

## Consejos:

- Si la luz no brilla, revise la conexion a tierra.
- Asegure que Ud. perforo el aislante del alambre y llego a los conductores de cobre.